

WHAT IS CLAIMED IS:

1. A printing apparatus for printing a print medium with a print head, comprising:

- 5 a tray on which to put the print medium;
 a tray guide removably mounted to the printing apparatus to support the tray so that it can be fed;
 detecting means for detecting whether or not the tray guide is mounted to the printing apparatus; and
10 control means for controlling the printing apparatus;

 wherein the control means changes its control on the printing apparatus according to a result of the detection by the detecting means.

15

2. A printing apparatus as claimed in claim 1, further including a carriage for carrying and moving the print head;

 wherein the control means controls a position of
20 the carriage according to the result of the detection by the detecting means.

3. A printing apparatus as claimed in claim 2,

 wherein the print head is removably mounted on the
25 carriage; and

 wherein, when the detecting means detects that the tray guide is mounted to the printing apparatus, the

control means prohibits the carriage from moving to a replacement position where the print head can be mounted to or dismounted from the carriage.

5 4. A printing apparatus as claimed in claim 2, further including a transport roller to transport the tray;

 wherein the control unit controls a driving of the transport roller according to the result of the
10 detection by the detecting means.

 5. A printing method for printing a print medium with a print head, comprising the steps of:

 removably mounting to a printing apparatus a tray
15 guide that supports a tray on which the print medium is placed so that the tray can be fed;

 detecting whether or not the tray guide is mounted to the printing apparatus by a detecting means; and

 changing a control on the printing apparatus by a
20 control unit according to a result of the detection by the detecting means.